

TC16-20-84

Nimi:	Yhdistelmätermostaatti Yhdistelmätermostaatti, 16A, anturilla, Impressivo IMPRESSIVO®
Tyyppi:	TC16-20-84
EAN:	6438199005973
Snro:	2619401
Kuvaus:	<p>Ecodesign-asetuksen täyttävä termostaatti, jossa on matala rakenne (upotussyvyys 20 mm). Termostaatti on esiohjelmoitu. Nimellisjännite 230 V AC \pm10% 50 Hz Lähtö 1 no ja liittimet 1.5 mm² - 4 mm² Kytkevätvirta 250 V AC / 16 (2) A, suojausluokka II ja koteloituiluokka IP21. Käyttölämpötila 0°C - 35°C ja varastointilämpötila -20°C - 70°C Kellon tarkkuus (20°C:ssa) < +/- 0,5 sek./pvm Tehonkulutus (standby) < 0,05 W Lattia-anturi NTC 10kΩ @25°C sekä ulkoinen ohjaus (EXT liitin) 230V AC / 10μA (sama vaihe).</p>
Pakkaus:	1/10
Yksikkö:	



ETIM

ETIM 7	EC011309 (EC011309)
ETIM 8	EC011309 (EC011309)

ETIM 8

Type of power supply	230 V
Connection	3-/4-wire
With receiver	no
Measuring range	5 ... 50 °C
External sensor	yes
With thermal feedback	yes
Control characteristic	P
Suitable for heating	yes
Number of heater outputs	1
Number of cooler outputs	
Selector switch for heating and heating with hot water	no
Sensor/feeler type	Resistance sensor
Temperature readable	yes

TC16-20-84

With display	yes
Type of clock	Week clock
Clock model	Digital
Overtime switch	no
Optimisation	yes
With tap water circuit	no
Operation	Button
Weather-dependent control system	no
Number of switching programmes	28
Max. contact voltage	250 V
Max. contact load	16 A
Degree of protection (IP)	IP21
Explosion-proof	no
RAL-number	9016
Width	71 mm
Depth	37.8 mm
Height	71 mm
Class of the temperature control	II
Standby power consumption (solstandby)	0.05 W