

H81381P3-W

Nimi: **Tuloyksikkö**
IP Videoulkotaulu PoE 3 nappia valkoinen

Tyyppi: H81381P3-W
EAN: 6955891809116

Snro:

Kuvaus: • Video camera with automatic day/night switchover and infrared LEDs to illuminate the night shots. • HD camera (1280 x 720 pixel). • Detection angle diagonal/horizontal/vertical: 139°/111°/73°. • Integrated status display via LED symbols (complies with DIN 18040). • Key module is backlit. • Integrated removal sensor (signals an alarm in the Smart Access Point as soon as a device is removed from the socket). • Suitable for surface-mounted or flush-mounted installation (Box is not included in the scope of delivery) • For surface-mounted installation with 41383S-.-03. • For flush-mounted installation with 41383F-.-03 • For mounting in plastered facades additionally with 41383PB-03. • Power supply via Power-over-Ethernet (PoE) 802.3af. • Alternative power supply 24 Volt DC, 330 mA. • Connection option for an electric door opener (18 V, 4 A Impuls, max. 250 mA continuous). • Floating door opener output (230 V AC, 3 A or 30 V DC, 3 A). • Alternative door opening function with MDRC IP switch actuator (H8304-03). • Connection option for external door sensor, for detecting the door status after the door opens. • Connection option for external door button for door opening. • Impact protection: IK07. • Front plate made of 3 mm white painted stainless steel. • Stamped labelling foil is enclosed. • Mounting tool is enclosed. • Protection class (device): IP 54 • Temperature range (device): -40 °C - 55 °C • Dimensions: (L x W x D): 277 mm x 135 mm x 18 mm

Pakkaus: 1/16

Yksikkö: KPL

